



# ANTOL 24



## PRODUCT DESCRIPTION

Powerful emulsifiable industrial degreaser.

## FEATURES & BENEFITS

- Especially suited for removing heavy industrial contaminants such as grease, lubricants, tar, asphalt and bitumen.
- Effortlessly cleans machine parts and metal surfaces.
- Formulated with powerful emulsifiers for optimal dilution with water.
- Absorbs about 5 times the volume of contamination (oil and grease).
- Flash point around 65°C.
- Contains aromatics.

## USAGE

For manual cleaning, preferably use undiluted. Allow to work for a short time, then let it evaporate, wipe off with a cloth or brush, or rinse off with water.

For high-pressure and spray cleaning, preferably dilute to 1%–2% (1:100–1:50) and apply at approximately 60°C. Apply evenly. Allow to work for a short time, then let it evaporate, wipe off with a cloth or brush, or rinse off with water.

## STORAGE

Keep package tightly closed and store under cool, but frost-free temperatures.

## RECYCLING

The empty packaging can be fully recycled if rinsed with water.

## AVAILABLE

Article code	Content	Packaging	Pallet-quantity
803-0009-002	10 liter	Drum	50 drums
803-0004-002	60 liter	Drum	6 drums
803-0002-002	200 liter	Barrel	2 barrels

## CERTIFICATES



## COMPOSITION

Contains: Hydrocarbons, C10-C13, N-Alkanes, Isoalkanes, Cyclics, Aromatics (2-25%).

## UFI CODE

HX62-60FY-800F-VPVK