



Product Specifications

AF903M



Air Filter, Primary

Fleetguard® AF903M axial seal primary air filter ensures a proper seal and prevent leaks to prevent airborne contaminants from reaching the combustion chamber.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

| | | | |
|---------------------|------------|-----------------------|-----------|
| Hauteur | 18.49 inch | ID le plus grand | 7.46 inch |
| Le plus grand OD | 13.84 inch | Flame Resistant Media | No |
| Flow Direction | Outside In | Type Seal | Axial |
| Efficiency Test Std | ISO 5011 | Full Life Efficiency | 99.95 |
| Rated Flow | 35 CU. m/m | Longueur | 0.72 in |

Product Comments

3311624 Bolt Seal Included

Related Parts

Replaces AF903

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved