



Product Specifications

FF5206

Fuel Filter, Spin-On



Fleetguard® FF5206 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Taille de filetage	13/16-12 UNS-2B	Gasket OD	3.49 inch
Gasket Inside Diameter	3.11 inch	Longueur	6.91 inch
Le plus grand OD	3.69 inch	Standpipe	No
Efficiency Test Std	SAE J905	Hydrostatic Burst Minimum	203.0 psi
Primary Particle Efficiency	17.3 micron (c) @ 99%	Rated Flow	379 L/min
Media Type	Cellulose		

Related Parts

For Upgrade, Use	FF5333
Replaces	FF206
Uses Service Part	3833200S

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved