



Product Specifications

FS1251



Fuel/Water Separator, Spin-On

Fleetguard® FS1251 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Taille de filetage	M16 X 1.5-6H INT	Longueur	5.63 inch
Le plus grand OD	3.02 inch	Gasket Inside Diameter	2.46 inch
Gasket OD	2.72 inch	Standpipe	YES
EMULSIFIED WATER SEPARATION	90%	Test Specification	ISO TR13353
Hydrostatic Burst Minimum	300.15 psi	Primary Particle Efficiency	17.3 micron (c) @ 96%

Related Parts

Replaces	FF5047	FS1226
Filter Used With	3311505S	
Upgrade Of	FF5052	
Is A Longer Version Of	FS1235	
Uses Service Gasket	3311919	

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved