



Product Specifications

FS1280



Fuel/Water Separator, Spin-On

Fleetguard® FS1280 premium fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Taille de filetage	13/16-18 UNS-2B	Le plus grand OD	3.69 inch
Longueur	6.49 inch	Gasket Inside Diameter	2.46 inch
Gasket OD	2.83 inch	Standpipe	NO
EMULSIFIED WATER SEPARATION	90 %	Hydrostatic Burst Minimum	300.15 psi
Test Specification	SAE J905	Primary Particle Efficiency	17.3 micron (c) @ 96%

Product Comments

Not suitable for Marine applications

Related Parts

Replaces	FF5038
Separator Version Of	FF5285
Uses Service Gasket	3311920

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved