



Product Specifications

LF777



Lube, By-Pass Spin-On

Fleetguard® LF777 premium spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Thread Size	1 3/8-16 UNF 2B	Gasket Inside Diameter	4.06 inch
Gasket OD	4.39 inch	Length	9.81 inch
Largest OD	4.57 inch	Pressure Valve	No
Media Type	Other	Rated Flow	10 L/m
Primary Particle Efficiency	30 micron (c) @ 99%		

Related Parts

Replaces	LF3326	LF3635	3308726S
Filter Used With	3304173S		
Uses Service Part	3318567S	3318566S	
Is European Version Of	LF3635		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved