



**Donaldson**  
FILTRATION SOLUTIONS

# Product Specifications

**B120376**



**AIR FILTER, PRIMARY DURALITE**

## Why Choose Donaldson DuraLite™ Air Cleaners?

Rugged, lightweight, self-supporting, and completely disposable combination air cleaner and filter.

- Function well under severe pulsation conditions, particularly two- and three-cylinder engines.
- Vibration-resistant media is secured into molded housings of rugged ABS plastic—so they don't fall apart as other designs might.
- Easy to install, durable, and reliable.
- Completely disposable — acceptable for normal trash pick-up (DuraLite should not be incinerated).

## Attributes

Outlet Diameter	200 mm (7.87 inch)
Body Diameter Maximum	317.5 mm (12.50 inch)
Body Length	400 mm (15.75 inch)
Efficiency Test Std	ISO 5011
Rated Flow LR	43.9 m <sup>3</sup> /min (1550 cfm)
Rated Flow MR	52 m <sup>3</sup> /min (1836 cfm)
Rated Flow HR	60 m <sup>3</sup> /min (2119 cfm)
Restriction LR	10 mbar (4.02 inch H <sub>2</sub> O)

Restriction MR	14.91 mbar (5.98 inch H2O)
Restriction HR	19.91 mbar (7.99 inch H2O)
Family	ECB
Primary Application	DETROIT DIESEL 0180941002
Type	Primary
Style	Round
Brand	DuraLite™

---

#### Packaged Dimensions

Packaged Length	0.315 m (12.60 inch)
Packaged Width	0.315 m (12.60 inch)
Packaged Height	0.532 m (21.26 inch)
Packaged Weight	4.022 kg (8.87 lb)
Packaged Volume	0.055 m3 (1.95 ft3)

---

#### Other Information

NMFC Code	069100-05
UPC Code	742330116609

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.