



Product Specifications

FF196



Fuel Filter, Spin-On

Fleetguard® FF196 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Taille de filetage	1-14 UNS-2B	Gasket Inside Diameter	2.46 inch
Gasket OD	2.83 inch	Le plus grand OD	3.69 inch
Longueur	5.90 inch	Standpipe	NO
Efficiency Test Std	SAE J905	Media Type	Cellulose
Hydrostatic Burst Minimum	145.0 psi	Primary Particle Efficiency	17.3 micron (c) @ 99%
Rated Flow	5.66 L/min		

Product Comments

NOTE: May also replace 702143-C1 if clearance is less than 8 inches. If greater than 8 inches use FF5020

Related Parts

For Upgrade, Use FS1220
Replaces FF197

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved