



Product Specifications

FF253



Fuel Filter, Spin-On

Fleetguard® FF253 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Efficiency Test Std	SAE J905	Hydrostatic Burst Minimum	239.9315 psi
Primary Particle Efficiency	16.6 micron (c) @ 98.7%	Le plus grand OD	3.67 inch
Longueur	3.14 in	Gasket OD	2.54 inch
Gasket Inside Diameter	2.22 inch	Taille de filetage	M20X1.5-6H
Media Type	Cellulose		

Related Parts

Replaces FF270

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property.

Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved