



# Product Specifications

## FF5156



### Fuel Filter, Spin-On

Fleetguard® FF5156 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](http://Fleetguard.com)

### Specifications

Gasket Inside Diameter	2.44 inch	Gasket OD	2.76 inch
Le plus grand OD	3.03 inch	Longueur	6.14 inch
Hydrostatic Burst Minimum	217.4999999999997 psi	Taille de filetage	M16X1.5-6H
Efficiency Test Std	ISO 19438	Primary Particle Efficiency	20 micron (c) @ 98.7%
Rated Flow	4 L/min	Media Type	Cellulose

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved