



Product Specifications

FF5633

Fuel Filter, Spin-On



Fleetguard® FF5633 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Efficiency Test Std	ISO 19438	Hydrostatic Burst Minimum	434.99999999999994 psi
Rated Flow	8.5 L/min	Le plus grand OD	4.33 inch
Longueur	10.2 in	Gasket OD	4.02 inch
Gasket Inside Diameter	3.71 inch	Taille de filetage	M32X1.5-6H
Media Type	Cellulose		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of

implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved