



Product Specifications

FS1006



Fuel/Water Separator, Spin-On

Fleetguard® FS1006 fuel water separator spin-on works to remove water and other particulates and ensures clean fuel is delivered to your engine.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Taille de filetage	1 1/4-12 UNS-2B	Longueur	12.32 inch
Le plus grand OD	4.74 inch	Gasket Inside Diameter	3.84 inch
Gasket OD	4.35 inch	Standpipe	YES
EMULSIFIED WATER SEPARATION	95 %	Media Type	Stratapore
		Test Specification	CECO ES14225
Hydrostatic Burst Minimum	144.99737549999998 psi		
Primary Particle Efficiency	10.1 micron (c) @ 98.7%		

Product Comments

Recommended for Cummins V28, KV38, and KV50 engines Stratapore Media

Related Parts

Filter Used With	3302367S
Upgrade Of	FS1216
For Upgrade, Use	FS19870
Uses Element	FH21402

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved