



Product Specifications

FF5114



Fuel Filter, Spin-On

Fleetguard® FF5114 spin-on fuel filter delivers superior performance using proven media technology, removing harmful contaminants. Fleetguard fuel filters ensure optimal fuel system protection to meet or exceed OEM specifications.

[View product on Fleetguard.com](http://Fleetguard.com)

Specifications

Taille de filetage	3/4-16 UNF-2B	Gasket Inside Diameter	2.26 inch
Gasket OD	2.52 inch	Le plus grand OD	3.32 inch
Longueur	3.22 inch	Standpipe	No
Efficiency Test Std	SAE J905	Hydrostatic Burst Minimum	203.0 psi
Primary Particle Efficiency	17.3 micron (c) @ 97%	Rated Flow	190 L/min
Media Type	Cellulose		

"Fleetguard is a brand of Atmus Filtration Technologies ("Atmus"). This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to customers of Atmus Filtration Technologies Inc. and its subsidiaries (collectively, "Atmus") "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Atmus does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Atmus directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2025 Atmus Filtration Technologies Inc. All Rights Reserved